

Compatible Video Display Modes for the AV42PD20

Model	Resolution	Vertical	Horizontal	Resolution	Vertical	Horizontal	Resolution	Vertical	Horizontal	Model	Resolution	Vertical	Horizontal	
		Frequency (Hz)			Frequency (Hz)			Frequency (Hz)				Frequency (Hz)		
IBM PC/AT compatible	640 x 480	59.9	31.5	800 x 600	56.3	35.2	1024 x 768	60	48.4	Apple Macintosh*	640 x 480	66.7	35	
		72.8	37.9		60.3	37.9		70.1	56.5			832 x 624	74.6	49.7
		75	37.5		72.2	48.1		75	60			1024 x 768	74.9	60.2
		85	43.3		75	46.9		85	68.7			1152 x 870	75.1	68.7
		100.4	51.1		85.1	53.7		100.6	80.5					
		120.4	61.3		99.8	63		60	64					
					120	75.7								

* Check the Macintosh display mode before connecting the plasma display. Use a D-sub 15-pin signal adapter (sold separately). Some Macintosh computers that use a mini D-sub 15-pin connection will require an RGB cable (sold separately).

Note that S-VGA, XGA and S-XGA signals are subject to compression to match the plasma display resolution.

- Attempting to use a non-standard signal (not listed above) can result in poor synchronization.
- Owing to the nature of plasma display technology, user adjustment of position etc. may be required even for one of the listed signals; this is because of possible timing errors in the computer hardware.
- Plasma display panel is made possible by using very advanced technology; however, due to the nature of plasma display manufacture, a few non-performing pixels are to be expected.
- This product comes with 3 prong grounded power plug. Make sure that the product is grounded securely before use.

IBM PC/AT is a registered trademark of International Business Machines, Inc. Apple Macintosh is a trademark of Apple Computer Inc.