

Headphones

Model	HA-G77	HA-G55	HA-G33	HA-G11	HA-DX3	HA-DX1	HA-V560	HA-P75	HA-CD68	HA-CD71F-B/G/Y
Driver Unit	50mm dia.	50mm dia.	40mm dia.	30mm dia.	50mm dia.	50mm dia.	40mm dia.	30mm dia.	30mm dia.	30mm dia.
Frequency Response	10 — 25,000Hz	14 — 25,000Hz	16 — 22,000Hz	18 — 22,000Hz	4 — 30,000Hz	5 — 30,000Hz	7 — 21,000Hz	10 — 23,000Hz	15 — 22,000Hz	8 — 22,000Hz
Nominal Impedance	32 ohms	32 ohms	32 ohms	32 ohms	90 ohms	45 ohms	32 ohms	32 ohms	32 ohms	32 ohms
Sensitivity	100dB/1mW	98dB/1mW	100dB/1mW	98dB/1mW	98dB/1mW	98dB/1mW	103dB/1mW	108dB/1mW	98dB/1mW	98dB/1mW
Cord Length	3.5m	3.5m	3.5m	3m	4m OFC	4m OFC	3m	1.5m	7m	2m
Max. Input Capability	100mW	100mW	50mW	50mW	100mW	100mW	50mW	50mW	50mW	50mW
Weight (without cord)	260g	270g	190g	150g	340g	300g	120g	125g	58g	48g
Plug	Gold plated	Gold plated	Gold plated	Nickel plated	Gold plated	Gold plated	Gold plated	Gold plated	Gold plated	Gold plated
Accessory	Plug adapter	Plug adapter	Plug adapter	Plug adapter	Plug adapter (screw-type)	Plug adapter	Plug adapter			

Model	HA-CD59	HA-37-BU/PN/GN/WY/L	HA-35	HA-33	HA-E5-BU/SL	HA-E3-BK/BU/RD/SL	HA-B27-SL	HA-B25-BU/SL	HA-B15-BU/SL	HA-B7-BU/SL
Driver Unit	30mm dia.	30mm dia.	30mm dia.	30mm dia.	30mm dia.	27mm dia.	30mm dia.	30mm dia.	30mm dia.	30mm dia.
Frequency Response	15 — 22,000Hz	17 — 25,000Hz	17 — 25,000Hz	17 — 25,000Hz	14 — 24,000Hz	18 — 24,000Hz	8 — 24,000Hz	8 — 20,000Hz	10 — 20,000Hz	15 — 20,000Hz
Nominal Impedance	32 ohms	32 ohms	32 ohms	32 ohms	32 ohms	32 ohms	32 ohms	32 ohms	32 ohms	32 ohms
Sensitivity	100dB/1mW	100dB/1mW	100dB/1mW	100dB/1mW	91dB/1mW	94dB/1mW	103dB/1mW	108dB/1mW	108dB/1mW	98dB/1mW
Cord Length	2m	1.5m	1.5m	1.5m	1.2m	1.2m	1.5m	1.5m	1.5m	1.5m
Max. Input Capability	50mW	50mW	50mW	50mW	30mW	30mW	30mW	30mW	30mW	30mW
Weight (without cord)	58g	43g	47g	43g	34g	26g	48g	54g	48g	46g
Plug	Gold plated	Nickel plated	Nickel plated	Nickel plated	Gold plated	Nickel plated	Gold plated	Gold plated	Gold plated	Gold plated

Model	HA-F90	HA-F70	HA-F50
Frequency Response	16 — 22,000Hz	16 — 22,000Hz	16 — 22,000Hz
Nominal Impedance	16 ohms	16 ohms	16 ohms
Sensitivity	103dB/1mW	103dB/1mW	103dB/1mW
Cord Length	1.2m	1.2m	1.2 m
Max. Input Capability	20mW	20mW	20mW
Weight (without cord)	6g	6g	6g
Plug	Gold plated	Gold plated	Nickel plated
Accessory	Travel pouch		

Model	TP-1
Type	Moving coil
Impedance	25 ohms
Sensitivity	116dB/1mW
Cord Length	3m with 3.5mm dia. miniplug
Max. Input Capability	50mW
Weight (without cord)	13g
Plug	Nickel plated

Model	HA-SU700
GENERAL	
Frequency Response	18 — 22,000Hz
Power Requirements	AA (R6P) battery x 2 (DC 3V)
Cord Length	7m
Weight (without cord)	280g (including battery)
WHEN SRS IS ON	
Input Impedance	500 ohms
Distortion	Less than 0.3% (at 1kHz)
Battery Running Time	Approx. 70 hours (when manganese battery is used) Approx. 140 hours (when alkaline battery is used)
WHEN SRS IS OFF	
Sensitivity	94dB/1mW

Model	HA-W500RF
GENERAL	
Modulation System	Stereo frequency modulation
Carrier Frequency	863 — 865MHz
Usable Area	Max. 100m (using JVC measurement system)
Frequency Response	30 — 15,000Hz
Distortion	Less than 4% (at 1kHz)
TRANSMITTER	
Power Requirements	DC 9V (with exclusive AC adapter)
Audio Input Terminal	3.5mm dia. Stereo miniplug
Input Impedance	25 k-ohms
Reference Input Level	300mV
Dimensions (W x H x D)	100 x 106 x 100mm (including antenna)
Weight	115g (without connection cord and AC adapter)
HEADPHONES	
Power Requirements	Rechargeable Ni-Cd battery (1.2V) x 2
Battery Running Time	20 hours (when charged for 24 hours)
Weight	280g (with installed batteries)