

Powered Subwoofer

Model	SX-DW303	
SPECIFICATIONS		
AMPLIFIER SECTION		
Amplifier	Digital Amplifier (PWM Type)	
Output Power	100 watts (4 ohms, 45Hz, 10% THD)	
Cut-Off Frequency	Variable (50Hz - 200Hz)/Fixed (150Hz)	
SPEAKER SECTION		
Type	Bass-Reflex	
Magnetically Shielded	●	
Speaker	16cm, Cone Woofer	
Honeycomb Structure Diaphragm	●	
Impedance	4 ohms	
Frequency Range	30Hz - 200Hz	
Terminals	RCA PIN	●
	Speaker Input	●
	Speaker Output	●
Volume Control	●	
Dimensions (W x H x D)	mm	217 x 393 x 376
Mass	kg	9,2

Model	SP-PW100	
SPECIFICATIONS		
AMPLIFIER SECTION		
Output Power	60W (10% T.H.D.)	
Crossover Frequency	Variable (50 - 200Hz)	
SPEAKER SECTION		
Type	Bass-Reflex	
Magnetically Shielded	●	
Speaker	16cm, Cone Woofer	
Impedance	4 ohms	
Frequency Range	25 - 200Hz	
Dimensions (W x H x D)	mm	226 x 315 x 376
Mass	kg	9,9